DCNM-MMD DCN multimedia Multimedia Device

www.boschsecurity.com





- ▶ 7" capacitive touchscreen
- ▶ Unobtrusive pluggable microphone
- ▶ Built-in two-way loudspeaker
- ▶ Video, meeting content and internet access
- Add functionality via software and 3rd party/custom apps

The Multimedia Device is essential for local and regional councils and is ideal when multimedia content is required. The multimedia device is easily plugged into, or removed from, the system using the system network cabling, which enables the system to be set up quickly and efficiently.

The multimedia device can be free-standing or fixed to the table using mounting screws.

The multimedia device can be remotely configured as chairperson or participant seat and has a remote switch off function for energy saving. It has perfect audio quality and a pluggable microphone (to be ordered separately).

Multimedia devices can be connected in a simple daisy-chain configuration. Alternatively, the devices can be connected in star configuration where each device is connected to a Power over Ethernet compatible switch with an individual standard CAT-5e (or better) cable. The connectors are at the bottom of the devices, ensuring a neat and clean system installation.

Functions

Controls and indicators

- Full color 7" capacitive-touch graphical display including:
 - Agenda and meeting data browsing.
 - Internet browsing.
 - Live video (e.g. showing the current speaker).
 - Meeting management for the chair person.
 - Headphones volume control.
 - Possibility for adding 3rd party android app.
 - Functionality can be increased by adding software.
- · Document retrieval:
 - MSWord (.doc, .docx).
 - Excel (.xls, .xlsx).
 - PowerPoint (.ppt, .pptx, .pps, .ppsx).
 - Portable Document Format (.pdf).
 - Rich Text Format (.rtf).
 - Plain text (.txt).
- Images codecs:
 - .jpg.
 - .gif.
 - .png.
 - .bmp.
 - .webp.

- · Audio codecs:
 - AAC (.aac,.3gp, .mp4, .m4a, .ts).
 - Flac (.flac).
 - Mp3 (.mp3).
 - Midi (.mid).
 - Forbis (.oog).
 - PCM (.wav).
- · Video codecs
 - H263 (.3gp, .mp4).
 - H264 (.3gp, .mp4).
 - MPEG4 (.3gp).
 - vp8 (.webm).
- · Pluggable microphone.
- Built-in 3M pixel camera for future use.
- Built-in two-way loudspeaker.
- Microphone on/off button or request-to-speak button.
- Microphone mute or chairperson priority button.
- Indicators showing: microphone on state, request-to-speak and possible-to-speak.
- Two-way speaker system.

Interconnections

- · Socket for pluggable microphone.
- 2x RJ45 compatible connection for system communication and power.
- 3.5 mm stereo jack for headphones, external microphone or headset microphone.
- · Hot plug-and-play.
- · Provision to attach a magnetic name card holder.

Parts included

Quantity	Components
1	DCNM-MMD DCN multimedia Multimedia Device

Technical specifications

General

Screen size	7 inch, 1024 x 600 pixels
Screen type	Capacitive multi touch
Operating system	Android 4.03

Electrical

Supply voltage	48 Vdc IEEE 802.3 at Type 2
Power consumption	12.5 W
Frequency response	100 Hz – 20 kHz (-3 dB at nominal level)
THD at nominal level	< 0.01 %
Dynamic range	96 dB (14-110 dBSPL)
Signal-to-noise ratio	66 dB with respect to nominal level headroom 30 dB

Audio inputs

Nominal microphone input	80 dB according IEC60914
Maximum microphone input	110 dB according IEC60914
External microphone nominal input	-38 dBV
External microphone maximum input	-25 dBV

Audio outputs

Laudan adam and autout	70 -ID CDI - 0 0 F
Loudspeaker nominal output	72 dB SPL @ 0.5 m
Loudspeaker maximum output	90 dB SPL
Headphone nominal output	-3 dBV
Headphone maximum output	0 dBV

Mechanical

Mounting	Tabletop
Dimensions (H x W x D)	75 x 312 x 175 mm (2.95 X 12.28 x 6.89 in)
Weight	1.85 kg (4.078 lb)
Color	Traffic black RAL 9017 Pearl light grey RAL 9022

Environmental

Operating temperature	0 °C to +35 °C (32 °F to +113 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Relative humidity	< 95 %, > 5%

Ordering information

DCNM-MMD DCN multimedia Multimedia Device

Multimedia conference device with capacitive touchscreen. Pluggable microphone to be ordered separately.

Order number **DCNM-MMD**

Accessories

DCNM-HDMIC DCN multimedia High Directive Microphone

Microphone for the DCNM-MMD DCN multimedia Multimedia Device.

Order number DCNM-HDMIC

DCNM-NCH DCN multimedia Name Card Holder (25 pcs)Order number **DCNM-NCH**

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 12000 Portland Avenue South Burnsville MN 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V. P.O. Box 80002 P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific:

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

China:
Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com